

No. AJD201200112

Date: JAN.19, 2012 Page 1 of 4

XIAMEN UGUARD COMPOSITE MATERIALS CO., LTD

NO.88 XIANGXING ROAD, TORCH HIGH-TECH ZONE, XIANG'AN, XIAMEN, CHINA

The following sample(s) was / were submitted and identified on behalf of the client as: Sample Name: POLYURETHANE FLAME RETARDANT PLASTICS P.O. / Ref No.: FDAY008

Test Requested:

To determine the performance of the sample when it is subjected to the conditions of test specified in UL 94, Tests for Flammability of Plastic Materials for Parts in Devices and Appliances, Vertical Burning Test For Classifying Materials V-0, V-1 or V-2

Test Results: -- See attached sheet --

Conclusion: According to the test results and the classification system, the tested sample, when tested at a normal thickness of 9.3mm, is assigned as "UL 94, V-2"

Test Period:

Sample Receiving Date : JAN.09, 2012 **Test Performing Date**

: JAN.09, 2012 TO JAN.18, 2012

Signed for and on behalf of SGS-CSTC Co., Ltd.

Allen Zou **Technical Supervisor**



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions. htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability interpartic to and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of the interpart of the document's subject to Terms and Conditions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from seriesing all thefm this and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any thrauthorized alteration of transaction of the content or appearance of this document is unavful and offenders may be prosecuted to the fullest extent of the law. University events of the secure to the sample(s) tested and such sample(s) are retained for 30 days only.

es Co., Ltd. | No.301, Yangguang Avenue, District 2, Sunlight Industrial Zone, Anji County, Zheijang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.cn.sgs.com f (86-572) 5018829 e sgs.china@sgs.com 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825



No. AJD201200112

2 Date: JAN.19, 2012 Page 2 of 4

I. Test conducted

This test was conducted in accordance with UL 94:2009, Tests for Flammability of Plastic Materials for Parts in Devices and Appliances, clause 8, 50W (20 mm) Vertical Burning Test; V-0, V-1, or V-2

II. Scope of test

The requirements of UL 94 cover tests for flammability of polymeric materials used for parts in devices and appliances. They are intended to serve as a preliminary indication of their acceptability with respect to flammability for a particular application. The final acceptance of the material is dependent upon its use in complete equipment that conforms with the standards applicable to such equipment.

III. Sample details

Material	Polyurethane Flame Retardant Plastics
Color	Transparent
Density	About 5.3kg/m ²
Thickness	9.3mm

IV. Conditioning

Prior to testing:

Five specimens were conditioned for at least 48 h at a temperature of 23±2 $^\circ\!\mathrm{C}$ and a relative humidity of 50±5%,

Five specimens were conditioned in a circulating air oven for 168 h at 70±1 $^{\circ}$ C and then cooled in the desiccator for at least 4 h at room temperature.

V. Test results:

1) Conditioned at: T:23±2℃ H :50±5 % 48 h

Specimen No.	t1 (seconds)	t2 (seconds)	t3 (seconds)	Whether or not specimens burn up to the holding clamp	Whether or not specimens drip flaming particles that ignited the cotton indicator	
1	1	0	0	No	Yes	
2	1	2	0	No	No	
3	0	1	0	No	Yes	
4	0	1	0	No	Yes	
5	0	0	0	No	Yes	

To be continued...

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions. htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability treatment on and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its inter centro and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of for exercising all thereins that soligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any Dnauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unlass of the solity to the sauth shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



es Co., Ltd. No.301,Yangguang Avenue, District 2, Sunlight Industrial Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.cn.sgs.com Laboratory, 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com



No. AJD201200112

Date: JAN.19, 2012

Page 3 of 4

2) Conditioned at: 70± 1 °C 168 h

Specimen No.	t1 (seconds)	t2 (seconds)	t3 (seconds)	Whether or not specimens burn up to the holding clamp	Whether or not specimens drip flaming particles that ignited the cotton indicator	
1	1	1	0	No	Yes	
2	0	1	0	No	Yes	
3	0	0	0	No	No	
4	1	0	0	No	Yes	
5	1	0	0	No	No	

Where, t1: Afterflame time after first flame application;

t2: Afterflame time after second flame application;

t3: Afterglow time after second flame application.

Note: Materials classified V-0, V-1 or V-2 shall comply with the following requirements

Criteria conditions	V-0	V-1	V-2
Afterflame time for each individual specimen t1 or t2	≤10s	≤30s	≤30s
Total after flame time for any condition set (t1 plus t2 for the 5 specimens)	≤50s	≤250s	≤250s
Afterflame plus afterglow time for each individual specimen after the second flame application (t2+t3)	≤30s	≤60s	≤60s
Afterflame or afterglow of any specimen up to the holding clamp	No	No	No
Cotton indicator ignited by flaming particles or drops	No	No	Yes

STATEMENTS:

The test results only to the ignitability of the sample or combination of materials under the particular condition of test. They are not intended as a means of assessing the full potential fire hazard of the materials or products in use.

The specimen was supplied by the sponsor and SGS-CSTC ANJI Branch was not involved in any selection or sampling procedure.

To be continued...

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions. htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability the request of this document is advised that information contained hereon reflects the Company's findings at the time of its interventions of this document is advised that information contained hereon reflects the Company's findings at the time of its interventions of the Company's sole responsibility is to its Clienta nd this document on the variate parties to a transaction from secretising all them only and bilgations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the Company. Any binauthorized alteration forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless other security is a subject to the fullest extent of the law. If the security is the security of the fullest extent of the law. If the security is the security of the security of the sample(s) tested and such sample(s) are retained for 30 days only. If the security is the security of the sample (so the sample(so th

中国·浙江·安吉县阳光工业园二区阳光大道301号

ods Laboratory.



No. AJD201200112

Date: JAN.19, 2012

Page 4 of 4

Photo Appendix:



End of Report





es Co., Ltd. No.301,Yangguang Avenue, District 2, Sunlight Industrial Zone, Anji County, Zhejjang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.cn.sgs.com s Laboratory 中国・浙江 · 安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com